

GV-Tower NVR System V2



Introduction

The GV-Tower NVR System V2 comes with 4 hot-swap drive bays for the storage of 24 TB. This system has two CPU options: Intel Core i3 and i5. It features the latest upgraded NVR system and 64-bit Microsoft Windows Embedded OS. GV-Tower NVR System V2 supports up to 32 channels of GV-IP devices or third-party IP devices (license required). You can also bring the surveillance on the HDTV with a HDMI cable. It is a towering, affordable, and efficient NVR system that you have ever seen.

Features

- Powered by Intel Core i3 or i5 Processor
- 64-bit Windows Embedded OS
- Support for GPU Decoding
- 4-bay hot-swap data HDD
- Maximum storage capacity of 24 TB
- Pre-installed SSD for recovery
- Dual Gigabit LAN ports
- 3-monitor display (VGA, DVI-D and HDMI outputs)
- Support for 3rd party IP devices
- Support for 32 channels (Pure IP solution)
- All-in-one solution (Live View, Playback, Recording, Backup, CMS)
- Video analysis
- Fisheye camera dewarping function
- Automatic connection to GV-IP devices
- H.265 / H.264 / MJPEG / MPEG4
- On-screen LED panel for HDD status
- Smart device access
- Multiple (31) languages

Packaging

- GV-Tower NVR System V2 x 1
- Keys for Hard Disk Safety Lock x 2
- Hard Disk Drive Screw x 16
- GV-IR Remote Control x 1
- GV-IR Remote Control Receiver x 1
- AC Power Cord x 1
- GV-Tower System V2 Quick Start Guide x 1

Specifications

Hardware

System		
CPU	Intel Core i3 Processor	
	Intel Core i5 Processor (optional)	
RAM	4 GB Dual Channels	
No. of HDD	4 (3.5" HDD; SATA3 interface)	
Internal Storage	64 GB (SSD)	
OS	64-bit Windows Embedded OS	
DirectX	11	
Power	250 W, 110-115 V, 60 Hz	
	250 W, 220-230 V, 50 Hz	
Connector	Ethernet	RJ-45, 10 / 100 / 1000 Mbps x 2
	Video Output	VGA, DVI-D and HDMI
	USB 2.0	Front: 2 ports
		Rear: 4 ports
USB 3.0	Rear: 2 ports	
Environment		
Operating Temp.	0 ~ 45 °C / 32 ~ 113 °F	
Humidity	0 ~ 80% RH (non-condensing)	
Physical		
Color	Silver	
Dimensions (W x H x D)	200 x 270 x 335 mm / 7.87 x 10.63 x 13.19 in	
Net Weight	8 kg / 17.64 lb (± 1 kg / 2.2 lb)	
Sensor and Alarm (Optional)		
GV-IO Box 4 Ports	4 inputs, 4 outputs	
GV-IO Box 8 Ports	8 inputs, 8 outputs	
GV-IO Box 16 Ports	16 inputs, 16 outputs	

Software

Video and Audio		
Model	GV-Tower NVR (GV)	GV-Tower NVR (3rd Party)
Video Input	32 channels	1, 2, 4, 6, 8, 10, 12, 16, 18, 20, 22, 24, 26, 28, 30, 32 channels (license required)
Audio Input	32 channels	1, 2, 4, 6, 8, 10, 12, 16, 18, 20, 22, 24, 26, 28, 30, 32 channels (license required)
Live View and Playback		
Image Control	Contrast / Brightness / Saturation / Hue	
Recording Mode	Round the Clock / Motion Detection / Sensor Detection / Pre & Post Recording / Schedule Recording	
Pre Recording	1~ 45 min.	
Instant Playback	10 sec. / 30 sec. / 1 min. / 5 min.	
Watermark	Supported	
Searching and Playback		
Search Method	Date / Time / Camera / Event Type	
Backup Type	DVD+R (DL) / DVD-R (DL) / DVD+R / DVD+RW / DVD-R / DVD-RW / CD-R / CD-RW	
Remote Monitoring		
Monitoring Environment	Web browser (IE, Chrome, Firefox and Safari)	
	Mobile device (Android Smartphone and tablet; iPad, iPhone and iPod Touch)	
Live View	Max. 32-channel multi views (Up to 200 channels connection to GV-Tower System V2)	
Network Type	LAN, WAN, Internet	
System Monitoring and Recovery		
Power Restoration	Automatic restart after power outage	
Monitoring	Two independent Watchdogs (Hardware Watchdog + Software Watchdog)	
Recovery	Automatic system rebuild from internal SSD.	
Language		
Type	Arabic / Bulgarian / Czech / Danish / Dutch / English / Finnish / French / German / Greek / Hebrew / Hungarian / Indonesian / Italian / Japanese / Lithuanian / Norwegian / Persian / Polish / Portuguese / Romanian / Russian / Serbian / Simplified Chinese / Slovakian / Slovenian / Spanish / Swedish / Thai / Traditional Chinese / Turkish	

Software License	
Free License	32 channels from GV-IP devices
Maximum License	32 channels from third-party IP devices
Increment for Each License	1 to 32 third-party IP cameras in increments of 2
Optional Combinations	N/A
Dongle Type	Internal

Note:

1. The Maximum License is a paid service.
2. It is required to enable the dual-stream function on GeoVision and third-party IP cameras to have the maximum number of channels supported. For single streaming third-party IP cameras, please see "Total Frame Rate and Max. No. of Channels Supported" below.
3. For backup function, you need to connect an external USB DVD/CD burner.
4. Product design and specifications are subject to change without notice.

Total Frame Rate and Max. No. of Channels Supported

For GV-IP Camera (Dual Streams)

Video Resolution	Dual Streams		Max. FPS	Intel Core i3 / i5	
	Stream 1 (H.264)	Stream 2 (H.264)		Total FPS	Full-Frame Channels
1.3 MP	1280 x 1024	320 x 256	30 fps	960 fps	32 ch
2 MP	1920 x 1080	448 x 252	30 fps	960 fps	32 ch
3 MP	2048 x 1536	320 x 240	20 fps	640 fps	32 ch
5 MP	2560 x 1920	320 x 240	10 fps	320 fps	32 ch

For GV-Fisheyes Camera (Single Stream De-warping)

Video Resolution	Single Stream (H.264)	Max. FPS	Intel Core i3		Intel Core i5	
			Total FPS	Full-Frame Channels	Total FPS	Full-Frame Channels
1.3 MP	1280 x 1200	15 fps	180 fps	12 ch	180 fps	12 ch
2 MP	1920 x 1080	15 fps	135 fps	9 ch	135 fps	9 ch
4 MP	2048 x 1944	15 fps	75 fps	5 ch	75 fps	5 ch
5 MP	2560 x 1920	10 fps	60 fps	6 ch	60 fps	6 ch

For Third-Party IP Camera (Single Stream GPU Decode)

Video Resolution	Single Stream (H.264)	Max. FPS	Intel Core i3		Intel Core i5	
			Total FPS	Full-Frame Channels	Total FPS	Full-Frame Channels
1.3 MP	1280 x 1024	30 fps	960 fps	32 ch	960 fps	32 ch
2 MP	1920 x 1080	30 fps	780 fps	26 ch	870 fps	29 ch
3 MP	2048 x 1536	20 fps	540 fps	27 ch	560 fps	28 ch
4 MP	2048 x 1944	15 fps	405 fps	27 ch	465 fps	31 ch
5 MP	2560 x 1920	10 fps	280 fps	28 ch	310 fps	31 ch

Options

GV-Data Capture V3 Box	GV-Data Capture V3 Box can integrate the GV-Tower DVR/NVR System V2 to an electronic POS system, while GV-Data Capture V3E Box can establish such integration through LAN or Internet.
GV-Hub V2	An easy way for serial port extension. This hub can add 4 RS-232/RS-485 serial ports through the GV-Tower DVR/NVR System V2's USB port.
GV-COM V2	This unit can add 1 RS-232/RS-485 serial port through the GV-Tower DVR/NVR System V2's USB port.
GV-COM V3	This unit can add 1 RS-485 port to your computer through a USB connector.
GV-IO Box (4 Ports V1.2)	GV-IO Box 4 Ports V1.2 provides 4 inputs and 4 relay outputs. It supports both DC and AC output voltages, and provides a USB port for PC connection.
GV-IO Box (8 Ports)	GV-IO Box 8 provides 8 inputs and 8 relay outputs, and supports both DC and AC output voltages. A USB port is also provided for PC connection.
GV-IO Box (16 Ports)	GV-IO Box 16 provides 16 inputs and 16 relay outputs, and supports both DC and AC output voltages. A USB port is also provided for PC connection.
GV-Joystick V2	GV-Joystick V2 facilitates the PTZ camera control. It can be either plugged into the GV-Tower DVR/NVR System V2 for independent use or connected to GV-Keyboard to empower the operation.
GV-Keyboard V3	GV-Keyboard V3 is designed to program and operate the system, and it can also be connected with PTZ cameras directly for PTZ control.

Overview



Front View



Rear View